

SUCTION CUPS / Flat Dual Lip Structure

LF200

Features and Strengths

Excellent lifting force in both horizontal and vertical application

Examples of use

Flat Metal Sheets & Glass, Veneer Sheets, Electronic Components
Marbles



Recommended Lifting Force (Max.)

Model	Volume (cm ³)	Lifting Force (Kg) - Perpendicular			Lifting Force (Kg) - Parallel		
		- 20 kPa	- 60 kPa	- 90 kPa	- 20 kPa	- 60 kPa	- 90 kPa
LF200	275.00	78.00 / 150.00	115.00 / 154.00	176.00 / 224.00	65.00	98.00	149.00

※ The lifting force above does not include safety factor

Material Specifications


Material	Hardness Shore (°)	Color	Temperature (°C)
NBR	60	Black	-20~110
Silicone	55	Red	-70~200
White Silicone	55	Translucent White	-70~200
White Silicone (FDA)	55	Translucent White	-70~200
High temp. Silicone	50	Blue	-70~280
Conductive Silicone	70	Smoky Black	-45~90
Urethane	60	Dark Green	0~100
Mark Free	75	Black	-10~100

Material Resistance

Description	NBR	Silicone	White Silicone	High temp. Silicone	Conductive Silicone	Urethane	Mark Free
Wear Resistance	Excellent	Good	Good	Good	Good	Excellent	Good
Oil	Excellent	Poor	Poor	Poor	Poor	Excellent	Excellent
Weather / Ozone	Fair	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent
Alcohol	Good	Good	Good	Good	Good	Fair	Good
Acid	Fair	Poor	Poor	Poor	Poor	Poor	Excellent


Dimension

[Unit : mm]



[With 12F fitting]

I Build an Ordering No.

LF200 -  : Pre-mounted fitting
 1. Suction Cup

1. Suction cup	Description	Weight (g)	Symbol
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, Nitrile (NBR)	767	LF200-N-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, Silicone	729.64	LF200-S-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, White silicone	745.06	LF200-WS-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, White silicone (FDA)	745.06	LF200-WS-12F (FDA)
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, High temperature silicone	793.15	LF200-HS-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, Conductive silicone	759.56	LF200-CS-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, Urethane	794.61	LF200-U-12F
	Flat and Dual lip structure suction cup, 200mm diameter, G1/2 female, Mark free	828.66	LF200-A-12F