# **SUCTION CUPS** / Oval Flat Bellow

## VOBF40x80



#### **Features and Strengths**

Over bellows shaped for handling long, narrow, curved and oily workpieces. The feet inside the cup provide an anti-slide

#### Examples of use

Automotive panels and doors, Metal sheets, Press line Carton box, Wood panel, Furniture



#### Recommended Lifting Force (Max.)

Model	Volume (cm³)	Min. Curvature Radius R(mm)	Lifting Force (Kg) - Perpendicular			Lifting Force (Kg) - Parallel		
			- 20 kPa	- 60 kPa	- 90 kPa	- 20 kPa	- 60 kPa	- 90 kPa
VOBF40x80	22.50	40.00	4.8	12.8	18.2	5.3	15.6	22.9

X The lifting force above does not include safety factor


#### Material Specifications

Material	Hardness Shore (°)	Color	Temperature (°C)
Polyurethane	60	Translucent Orange	0~60

#### Material Resistance

Description	Polyurethane		
Wear Resistance	Excellent		
Oil	Excellent		
Weather / Ozone	Excellent		
Alcohol	Fair		
Acid	Fair		

# | Dimension [Unit:mm]



[With M10M fitting]

[With 14M fitting]

[With 18M fitting]



# Build an Ordering No.

VOBF40x80 - (

: Pre-mounted fitting

## 1. Suction Cup

1. Suction cup	Description	Weight (g)	Symbol
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, M10xP1.5 male Fitting	39.44	VOBF40x80-PU-M10M
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, G1/8 female Fitting	41.77	VOBF40x80-PU-18F
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, G1/8 male Fitting	39.83	VOBF40x80-PU-18M
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, G1/4 female Fitting	37.38	VOBF40x80-PU-14F
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, G1/4 male Fitting	41.02	VOBF40x80-PU-14M
	Oval flat bellow suction cup, 40x80mm diameter, Polyurethane, G3/8 female Fitting	40.7	VOBF40x80-PU-38F